

Portraits

Through Body Porcelain Matte - Rectified

Inspired by five extraordinary stones, the Portraits series portrays the instinctive beauty and strong character of natural stone in a versatile porcelain collection.

ecotile

PRE-CONSUMER

RETAIL PRICING LISTED



Comblanchien

| Stocked Sizes | Price /sf | Price /pc |
|---|-----------|-----------|
| 12"x 24" Matte | \$10.95 | \$21.90 |
| 24"x 24" Matte | \$11.95 | \$47.80 |
| 2"x 2" Matte Mosaics (12"x 12" mesh sheet) | \$32.95 | \$32.95 |
| 120 cm x 278 cm / 47" x 109" Matte Slabs* | \$22.99 | \$823.91 |



Inspire, Design, Create.
www.amestile.com/collections/portraits

All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.

Portraits

Through Body Porcelain Matte - Rectified



Comblanchien

| | 12"x 24" Matte | 24"x 24" Matte | 2"x 2" Matte Mosaics | 120 cm x 278 cm 47" x 109" Matte Slabs |
|--------------|-------------------|-------------------|-------------------------|--|
| \$ / sf | \$10.95 | \$11.95 | \$32.95 | \$22.99 |
| \$ / ea | \$21.90 | \$47.80 | \$32.95 | \$823.91 |
| Comblanchien | POCBM1224 | POCBM24 | POCBM2 | POCBM120278 |

All sizes are approximate and items are sold by piece.

Caution: Dark grout on light coloured tiles can scratch or stain the surface, please test a separate area before grouting your space.

Recommended Applications

W-Wall F-Floor

| | Shower | Steam | Light Commercial | Medium Commercial | Heavy Commercial | Residential | Outdoor |
|-------|--------|-------|------------------|-------------------|------------------|-------------|---------|
| Matte | W F | W F | W F | W F | W F | W F | W F |
| Slabs | W F* | W F* | W F* | W F* | W | W F* | W |

*Only for use on concrete substrates

Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks. All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.

Technical Specifications

Product specifications are supplied by the manufacturer and are subject to change without notice.

| V Rating (Variation) | Breaking Strength (ISO 10545-4) | Resistance to Deep Abrasion (ISO 10545-6) | Slip Resistance | Frost Resistance (ISO 10545-12) | Country of Origin | Ecotile |
|---|---------------------------------|--|----------------------|---------------------------------|-----------------------|------------------|
| V2 - Slight Variation | ≥1300 N, 700 N (Slabs) | ≤ 145 mm ³ | DCOF >0.55 R9 | Yes | Italy | Yes |
| Number of Faces | Thickness | Resistance to Surface Abrasion (ISO 10545-7) | Moisture Rating (MR) | MOHS (Hardness Scale) | PEI (Wear Resistance) | Recycled Content |
| 12"x 24" - 35 24"x 24" - 30 Slabs - 4 | 9mm 6mm (Slabs) | — | 1 - Impervious | — | Class 4 | Pre-Consumer |

Ames makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your Ames Sales Consultant for current prices.



Inspire, Design, Create.
www.amestile.com/collections/portraits