

Bera & Beren

Ceramic Wall Tile - Rectified
Through Body Porcelain - Rectified

Inspired by Portuguese and
Catalan Limestones, mixed with
contemporary shapes and textures.




Biscuit



Dark Grey



Light Grey



White

RETAIL PRICING LISTED

Stocked Sizes	Price /sf	Price /pc
12"x 36" Dot / Saw / Six (Wall Only)	\$13.95	\$40.46
18"x 36" Matte	\$13.95	\$60.54



Bera & Beren

Ceramic Wall Tile - Rectified
Through Body Porcelain - Rectified

Wall



Biscuit Dot




Light Grey Dot




Dark Grey Dot



White Dot



Biscuit Saw



Light Grey Saw



Dark Grey Saw



White Saw



Biscuit Six




Light Grey Six



Dark Grey Six




White Six



	12"x 36" Dot (Wall Only)	12"x 36" Saw (Wall Only)	12"x 36" Six (Wall Only)	18"x 36" Matte (Floor)
\$ / sf	\$13.95	\$13.95	\$13.95	\$13.95
\$ / ea	\$40.46	\$40.46	\$40.46	\$60.54
Biscuit	BBBCD1236	BBBCS1236	BBBCX1236	BBBC1836
Light Grey	BBLGD1236	BBLGS1236	BBLGX1236	BBLG1836
Dark Grey	BBDGD1236	BBDGS1236	BBDGX1236	BBDG1836
White	BBWHD1236	BBWHS1236	BBWHX1236	BBWH1836

· Alternate sizes, textures, décor and trim pieces may also be available for special order. Contact your sales consultant for more information.
· Shading and variation is inherent in ceramics and natural stone. Please inspect before installing, no claims accepted after installation.

Floor




Biscuit Matte



Light Grey Matte



Dark Grey Matte



White Matte

Recommended Applications

W-Wall F-Floor

	Shower	Steam	Light Commercial	Medium Commercial	Heavy Commercial	Indoor	Outdoor
12"x 36"	W	W	W	W	W	W	W
18"x 36"	W F	W F	W F	W F	W F	W F	W F

Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks. All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.

Caution: Dark grout on light coloured tiles can scratch or stain the surface, please test a separate area before grouting your space.

Technical specifications

V Rating (Variation)	Breaking Strength (ISO 10545-4)	Resistance to Deep Abrasion (ISO 10545-6)	Slip Resistance	Frost Resistance (ISO 10545-12)	Country of Origin	Ecotile
V2 - Slight Variation	>600 N (Wall) 1300N (Floor)	<175 mm ³ (18"x 36" Only)	DCOF >0.55 (18"x 36" Only)	Yes (18"x 36" Only)	Spain	Yes
Number of Faces	Thickness	Resistance to Surface Abrasion (ISO 10545-7)	Moisture Rating (MR)	MOHS (Hardness Scale)	PEI (Wear Resistance)	Recycled Content
—	9mm	—	MR4 (12"x 36") MR1 (18"x 36")	—	—	—

All images are for reference only and may not match physical product exactly. All product specifications are supplied by the manufacturer and are subject to change by the manufacturer without notice to you or to Ames Tile & Stone Ltd. Ames makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your Ames Sales Consultant for current prices.



Inspire, Design, Create.
www.amestile.com/beraberen