



# VERSA 7.5 SERIES



## VERSA 7.5 LUXURY CLICK VINYL FLOORING



Dove **VYVDV748**



Sea Salt **VYVSS748**



Aspen **VYVAP748**



Coastal Path **VYVCH748**



Camel **VYVCM748**



Buckskin **VYVBK748**



Hyde **VYVHY748**



Skyfall **VYVSA748**

### RETAIL PRICING LISTED

Stocked Sizes	Price /sf	Price /box
7" x 48"	\$7.95	\$149.14




Norway **VYVNW748**



Caramel **VYVCR748**



Lead **VYVLD748**



Heirloom **VYVHL748**



Resistance to Radiant Heat -

In slab, radiant heat only.  
Cannot use with mat, mesh or cable radiant heat  
(i.e. Nuheat & Ditra-Heat).

For more info, visit: [www.amestile.com/versa75](http://www.amestile.com/versa75)



# VERSA 7.5 TRIMS SERIES

## T Moulding $1\frac{3}{4}'' \times 94\frac{1}{2}''$



## Stair Nosing $5\frac{1}{8}'' \times 94\frac{1}{2}''$ - Nosing L = 1" Nosing W = 5/8"



## Reducers $1\frac{11}{16}'' \times 94\frac{1}{2}''$








Resistance to Radiant Heat -  
In slab, radiant heat only.  
Cannot use with mat, mesh or cable radiant heat  
(i.e. Nuheat & Ditra-Heat).

### RETAIL PRICING LISTED









Stocked Sizes	Price /pc
Reducer	\$39.95
T Moulding	\$39.95
Stair Nosing	\$69.95

# VERSA 7.5 SERIES












## Technical Data and Options

	Overall Thickness	0.295" (7,5 mm)
	Wear Layer Thickness	0.020" (0,50 mm)
	Plank Size	7" x 48" (18 cm x 122 cm)
	Packaging	8 planks/18.76 Sq.f./32.5 lbs (14.75 Kg)/Box
	Installation	Valinge 5G Drop Lock Floating Installation System



## Construction

	ASTM F1700, Class III, Type B	Residential   • Section 5.5.1 Medium Commercial Applications	
	100% Recyclable	WPC Core Structure with Attached Acoustic Pad	
	Printed Design	Hi-Definition natural wood visual embossing	
	Bevel Edge Profile	Four Sides	
	Phthalate Safe	EN 14372	Compliant
	Anti-Bacterial	ASTM G21 No Growth	Compliant
	Maintenance	A Ceramic bead polyurethane protection surface, with Sanitec® Ultra Violet cured to protect against wear, offers ease of maintenance and superior stain resistance.	

## Performance

	Abrasion resistance	ASTM D4060	EN 660-2 Group T	Excellent, Scratch Resistant
	Static Load Limit / Residual Indentation	Exceeds ASTM F970 Surpasses / 1500 psi EN 433 / ≥ 0,10 mm		Pass
	Resistance Caster Chair	EN 425: Suitable for office chairs with casters		Pass
	Dimensional Stability	ASTM F2199	0.01 - 0.03 %	Pass / Exceeds
	Chemical Resistance	ASTM F925	No Change	Pass
	Resistance to Radiant Heat	EN12524	0.25 W/mK, Max 77° F (25° C)	In slab, radiant heat only. Cannot use with mat, mesh or cable radiant heat (i.e. Nuheat & Ditra-Heat).
	Impact Insulation Class	ASTM E989 (ASTM E492)	IIC 73	Exceeds
	Sound Transmission Class	ASTM E90 (ASTM E413)	STC 67	Exceeds
	Slip Resistance	ASTM D2047	ADA Requirement	Compliant
	Fire Test Data – Flame Spread	ASTM E648	0.45 watt/cm <sup>2</sup> or more	Class I
	Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Compliant
	Fire Test Data – Canada	CAN/ULC S-102.2	CDN Building Code	Compliant

## Supplement and Environment

	Indoor Air Quality	FloorScore	Certification Guidelines	SCS-FS-04221/2018
	Low Emitting Material	In Compliance with CDPH/EHLB Standard Method v1.1-2010		
	Plants Certifications	ISO 14001, ISO 9002, OHSAS 18001		Certified

## Limited Warranty

10 Year Commercial / Lifetime Residential



VERSA 7.5


# VERSA 7.5 SERIES



## VERSA 7.5 LUXURY CLICK VINYL FLOORING



Carrara **VYVCA1224**



Snowfall **VYVSF1224**



Drift **VYVDR1224**



Battleship **VYVBA1224**



Tweed **VYVTD1224**



Truffle **VYVTF1224**



Creekside **VYVCS1224**



Magnet **VYVMG1224**



Orion **VYVOR1224**



Resistance to Radiant Heat

In slab, radiant heat only.  
Do not use with mat, mesh or cable radiant heat (i.e. Nuheat & Ditra-Heat).






### RETAIL PRICING LISTED

Stocked Sizes	Price /sf	Price /box
12"x 24"	\$7.95	\$154.07









For more info, visit: [www.amestile.com/versa](http://www.amestile.com/versa)

# VERSA 7.5 SERIES













## Technical Data and Options

 Overall Thickness	0.295" (7,5 mm)
 Wear Layer Thickness	0.020" (0,50 mm)
 Tile Size	12" x 24" (30 cm x 60 cm)
 Packaging	10 tiles/19.38 Sq.f./33.66 lbs (15.30 Kg)/Box
 Installation	Välinge 5G Drop Lock Floating Installation System




## Construction

 ASTM F1700, Class III, Type B	Residential   • Section 5.5.1 Medium Commercial Applications	
 100% Recyclable	WPC Core Structure with attached Acoustic Pad	
Printed Design	Hi-Definition abstract and natural stone visual embossing	
 Bevel Edge Profile	Four Sides	
 Phthalate Safe	EN 14372	Compliant
 Anti-Bacterial	ASTM G21 No Growth	Compliant
 Maintenance	A Ceramic bead polyurethane protection surface, with Sanitec® Ultra Violet cured to protect against wear, offers ease of maintenance and superior stain resistance.	

## Performance

 Abrasion resistance	ASTM D4060	EN 660-2 Group T	Scratch Resistant
 Static Load Limit / Residual Indentation	Exceeds ASTM F970 / 1500 psi EN 433 / ≥ 0,10 mm		Pass
 Resistance Caster Chair	EN 425: Suitable for office chairs with casters		Pass
 Dimensional Stability	ASTM F2199	0.01 - 0.03 %	Pass / Exceeds
 Chemical Resistance	ASTM F925	No Change	Pass
 Resistance to Radiant Heat	EN12524	0.25 W/mK, Max 77° F (25° C)	Suitable for heated floors
 Impact Insulation Class	ASTM E989 (ASTM E492)	IIC 73	Exceeds
 Sound Transmission Class	ASTM E90 (ASTM E413)	STC 67	Exceeds
 Slip Resistance	ASTM D2047	ADA Requirement	Compliant
 Fire Test Data – Flame Spread	ASTM E648	0.45 watt/cm <sup>2</sup> or more	Class I
 Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Compliant
 Fire Test Data – Canada	CAN/ULC S-102.2	CDN Building Code	Compliant

## Supplement and Environment

 Indoor Air Quality	FloorScore	Certification Guidelines	SCS-FS-04221/2018
 Low Emitting Material	In Compliance with CDPH/EHLB Standard Method v1.1-2010		
 Plants Certifications	ISO 14001, ISO 9002, OHSAS 18001		Certified

## Limited Warranty

 10 Year Commercial / Lifetime Residential
--