



RELIANT 2.0


RELIANT 2.0 SERIES



RELIANT 2.0 VINYL FLOORING




Arbor **VYRAR748**



Bristol **VYRBR748**



Compass **VYRCP748**




Debutante **VYRDB748**

RETAIL PRICING LISTED		
Stocked Sizes	Price /sf	Price /box
7.25" x 48"	\$2.95	\$156.85

For more info, visit: www.amestile.com/reliant20








Mason **VYRMS748**












Sutter **VYRST748**

RELIANT 2.0 SERIES













Technical Data and Options

 Overall Thickness	0.080" (2,0 mm)
 Wear Layer Thickness	0.012" (0,30 mm)
 Plank Size	7.25" x 48" (18,4 cm x 122 cm)
 Packaging	22 planks/53.17 Sq.f./42.4 lbs (19.27 Kg)/Box
 Installation	Full Spread Adhesives




Construction

 ASTM F1700, Class III, Type B	Light Commercial   	
 100% Pure solid vinyl	100% Recyclable	
Printed design	Hi-Definition natural visual and embossing options	
 Bevel edge profile	Four Sides	
 Phthalate Safe	EN 14372	Compliant
 Anti-Bacterial	ASTM G21 No Growth	Compliant
 Maintenance	UV-urethane antimicrobial, durable finish for a no wax easy maintenance	

Performance

 Abrasion resistance	ASTM D4060	EN 660-2 Group T	Excellent
 Static Load Limit / Indentation	ASTM F970	1500 PSI	Exceeds 250 PSI
 Resistance Castor Chair	EN 425 : suitable for office chairs with castors		Pass
 Dimensional Stability	ASTM F2199	Excellent	Pass
 Chemical Resistance	ASTM F925	Excellent	Pass
 Resistance to Radiant Heat	EN 12524	0.25 W/mK, Max 77° F (25° C)	Suitable for heated floors
 Impact Insulation Class	ISO 717-2	5 dB	Meets
 Sound Transmission Class	NF S 31-074	Class B	Meets
 Slip Resistance	ASTM D2047	ADA Requirement	Exceeds
 Fire Test Data – Flame Spread	ASTM E648	0.45 watt/cm ² or more	Class I
 Fire Test Data – Smoke Evolution	ASTM E662	450 or less	Meets
 Fire Test Data – Canada	CAN/ULC S-102.2	CDN Building Code	Compliant

Supplement and Environment

 Indoor Air Quality	FloorScore	Certification Guidelines	SCS-EC10.3 2014
 Certified Low Emitting Adhesives	SCAQMD	Rule #1168	Meets
 Plants Certifications	ISO 14001, ISO 9002, OHSAS 18001		Certified

Limited Warranty

 10 year Light Commercial / Lifetime residential
--