




2 CM THICK TILE THROUGH BODY PORCELAIN PAVERS

BASALTINA



Slate Grey



Granite



Charcoal

*6-8 weeks delivery time. Please contact an Ames Consultant for more information.

TRAVERTINE



Crema



Light

SLATE



Slate

WHY USE 2CM THICK PORCELAIN TILE?

- No need to seal
- High abrasion and stain resistance
- Withstand extreme temperature changes (-50°C to +60°C)
- Durable — with high breaking points and wear resistance
- Less than 10lbs per sq. ft. — ideal for rooftop applications
- No efflorescence
- Always “true to size” resulting in quick and easy installation
- High COF — good for traffic areas with slip concern

RETAIL PRICING LISTED

Stocked Size	Price /sf	Price /pc
24" x 24"	\$15.95	\$63.80

For more info, visit:
www.amestile.com/landstone2cm

Combining the essence of stone pavers with the performance and versatility of porcelain.

LANDSTONE 2 CM SERIES



	24" x 24"
\$/ sf	\$15.95
\$/ pc	\$63.80

BASALTINA

GRANITE	BST02
CHARCOAL	BST01
SLATE GREY	BST03

SLATE

SLATE	SLT015G
-------	---------

TRAVERTINE

CREMA	TRV01
LIGHT	TRV02


Alternate sizes, textures, décor and trim pieces may also be available for special order. Contact your sales consultant for more information.

*6-8 weeks delivery time. Please contact an Ames Consultant for more information.

BASALTINA



Slate Grey



Granite



Charcoal

TRAVERTINE



Crema



Light



Slate

THICK TILE OPPORTUNITIES

- Patios • Sidewalks • Balconies • Pool decks • Courtyards • Roof tops • Building façades • Driveways • Wineries • Sports arenas

RECOMMENDED APPLICATIONS

		Shower	Steam Shower	Light Commercial	Medium Commercial	Heavy Commercial	Indoor	Outdoor
24" x 24"	WALL	✓	✓	✓	✓	✓	✓	✓
	FLOOR	✓	✓	✓	✓	✓	✓	✓

Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks. All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.

TECHNICAL SPECIFICATIONS

V Rating (Variation)	Breaking Strength (ISO 10545-4)	Resistance to Deep Abrasion (ISO 10545-6)	Slip Resistance	Frost Resistance (ISO 10545-12)	Country of Origin	Ecotile
V2-V3 – Slight to Moderate Variation	> 8000 N	145 mm ³	DCOF >0.55	Yes	China	No
Number of Faces	Thickness	Resistance to Surface Abrasion (ISO 10545-7)	Moisture Rating (MR)	MOHS (Hardness Scale)	PEI (Wear Resistance)	Recycled Content
—	3/4" or 20mm	—	1 - Impervious	—	—	0%

All images are for reference only and may not match physical product exactly. All sizing is nominal and all product specifications are supplied by the manufacturer and are subject to change by the manufacturer without notice to you or to Ames Tile & Stone Ltd. Ames makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your Ames Sales Consultant for current prices.



Inspire. Design. Create.
www.amestile.com/landstone2cm

Shading and variation is inherent in ceramics and natural stone. Please inspect before installing, no claims accepted after installation.