
3D Bars Glazed Ceramic Wall Tiles


This collection merges small-scale geometry with surfaces that transform in light and shadows.











Stocked Sizes	Price /sf	Price /pc	
5"x 10" Bevel (Matte & Gloss)	\$26.91	\$9.06	
5"x 10" Diamond (Matte & Gloss)	\$26.91	\$9.06	

*Matte only available in Quartz colour







All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.

3D Bars Glazed Ceramic Wall Tiles



Quartz Bevel Gloss



Quartz Diamond Gloss



Quartz Bevel Matte



Quartz Diamond Matte



Emerald Bevel Gloss



Emerald Diamond Gloss



Jade Diamond



Jade Bevel Gloss



Sapphire Bevel Gloss



Sapphire Diamond Gloss



Onix Bevel Gloss



Onix Diamond Gloss









Pearl Diamond Gloss

	5"x 10" Bevel Gloss	5"x 10" Bevel Matte	5"x 10" Diamond Gloss	5"x 10" Diamond Matte	
\$ / sf	\$26.91	\$26.91	\$26.91	\$26.91	
\$ / ea	\$9.06	\$9.06	\$9.06	\$9.06	
Emerald	3DBBEMG510		3DBDEMG510		
Jade	3DBBJDG510		3DBDJDG510		
Onix	3DBBONXG510		3DBDONXG510		
Quartz	3DBBQRG510	3DBBQRM510	3DBDQRG510	3DBDQRM510	
Sapphire	3DBBSPHG510		3DBDSPHG510		
Pearl			3DBDPRLG510		

These tiles are meant to be grouted to achieve a mosaic look.

The recommended grout joint in between tiles is 1.5mm to be consistent with the 1.5mm pre-scored grout joint of the tile.

Use Prism grout for best results.

All sizes are approximate and items are sold by piece.

Caution: Dark grout on light coloured tiles can scratch or stain the surface, please test a separate area before grouting your space.

Recommended Applications



Shower



Steam



Light Commercial



Medium Commercial



Heavy Commercial



Residential



Outdoor

Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks. All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.

Technical Specifications

Product specifications are supplied by the manufacturer and are subject to change without notice.

V Rating (Variation)	Breaking Strength (ISO 10545-4)	Resistance to Deep Abrasion (ISO 10545-6)	Slip Resistance	Frost Resistance (ISO 10545-12)	Country of Origin	Ecotile
V1 - Uniform Appearance	≥600 N	_	_	No	Spain	Yes
Number of Faces	Thickness	Resistance to Surface Abrasion (ISO 10545-7)	Moisture Rating (MR)	MOHS (Hardness Scale)	PEI (Wear Resistance)	Recycled Content
_	11mm	_	4 - Non Vitreous	_	_	56%

Ames makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your Ames Sales Consultant for current prices.



$3D\,Bars$ Additional Information



To ensure correct alignment of the joints, it is recommended that all pieces be placed in the same direction. To do this, ensure the arrows on the back of the tile are all going the same direction.

HOW TO CREATE ROUNDED CORNERS

