

GLAZED CERAMIC MOSAIC WALL TILES

FOLIA & ATELIER

Folia and Atelier bring sculptural texture and refined geometric design together to create elegant feature walls with lasting visual impact.

DIGITAL



CATALOG

Click or Scan
QR Code

COLOUR SCHEMES & PATTERNS

ecotile



Atelier White
3D Mosaic



Folia White 3D
Diamond Mosaic



Atelier Almond
3D Mosaic



Folia Taupe 3D
Diamond Mosaic

Atelier Almond 3D Diamond Mosaic



Folia White 3D Mosaic



All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.

AMES TILE & STONE

GLAZED CERAMIC MOSAIC WALL TILES


FOLIA & ATELIER



12 x 16”
Atelier White 3D Diamond Mosaic
ATWHM



12 x 16”
Atelier Almond 3D Diamond Mosaic
ATALM



10 x 12”
Folia White 3D Mosaic
FLWHM



10 x 12”
Folia Taupe 3D Mosaic
FLTPM

	12 x 16” 3D Mosaic			10 x 12” 3D Diamond Mosaic		
	Price /sf	Price /pc	Box Qty.	Price /sf	Price /pc	Box Qty.
	\$69.95	\$85.83	8 Each	\$119.95	\$100.71	8 Each
Atelier White				ATWHM		
Atelier Almond				ATALM		
Folia White	FLWHM					
Folia Taupe	FLTPM					



All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.

GLAZED CERAMIC MOSAIC WALL TILES

FOLIA & ATELIER

RECOMMENDED APPLICATIONS

	Wall	Floor		Wall	Floor
 Shower	●		 Light Commercial	●	
 Steam			 Medium Commercial	●	
 Residential	●		 Heavy Commercial	●	
 Fireplace/ Feature Wall	●		 Outdoor		
			 Pool		

TECHNICAL SPECIFICATIONS

V Rating (Variation)	V2 – Slight Variation	Number of Faces	1
Thickness	Thinnest: 9.5 mm Thickest: 14.5 mm	Moisture Rating (MR)	4 – Non-Vitreous
Breaking Strength	> 35 N /mm ² , > 1300 N	Frost Resistance	No
Ecotile	No	Country of Origin	China

^A Only Linen colour suitable for Residential Floors.

SPACERS: Due to the nature of the material, there may be dimensional variations between pieces. For optimal results, please use 1.5 mm (0.06”) spacers.

GROUTING: The choice of using a quality grout is crucial. We recommend Custom Building Products Prism SCG.

MAINTENANCE & CLEANING: As a general guideline, powder detergents should not be used, nor wire wool or abrasive materials. Generally, a sponge will be sufficient with warm water and liquid neutral soap. Then rinse.

Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks.

All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.

Product specifications are supplied by the manufacturer and are subject to change without notice. Ames makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your Ames Sales Consultant for current prices.