

Manor

Luxury Vinyl Planks
Glue Down Installation

Durability with Style

Create a lasting look in your space with this flexible product that limits sound transmission.




Bradley



Charleston



Devonshire



Hardwick



Kentwell



Stokesay

RETAIL PRICING LISTED

Stocked Sizes	Price /sf	Price /box
7.25" x 48" x 4.0mm	\$6.95	\$201.45



Inspire, Design, Create.
www.amestile.com/lvf-composite/manor


All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.

Manor

Luxury Vinyl Planks
Glue Down Installation



1. **PUR / UV Cured Protection**
PurKleen™ Ceramic Bead Protection
2. **Transparent Wear Layer**
0.50mm (20mil), Micro Bevel Edge
3. **Printed Hi-Definition Design**
Natural Wood Patterns
4. **100% Pure PVC Core**
100% Waterproof
5. **Fiberglass Grid/Mesh**
Enhanced Stability
6. **Acoustic Layer**
Sound Rating: 73 IIC, High Density
7. **Backing Layer**
Flexible & Durable



	7.25" x 48"
\$ / sf	\$6.95
\$ / box	\$201.45
Bradley	VYMBD748
Charleston	VYMCT748
Devonshire	VYMDS748
Hardwick	VYMHW748
Kentwell	VYMKW748
Stokesay	VYMSK748




Bradley



Charleston




Devonshire



Hardwick



Kentwell



Stokesay






Looking for trims? Try Schluter **VINPRO** Visit schluter.ca for more

All images are for reference only and may not match physical product exactly. Shading and variation is inherent in ceramics and natural stone. Please inspect all products before installing, no claims accepted after installation.








Inspire, Design, Create.
www.amestile.com/lvf-composite/manor













TECHNICAL SPECIFICATIONS / CARACTÉRISTIQUES TECHNIQUES

	Total Thickness / Épaisseur	4.0 mm
	Wear Layer / Couche d'usure	0.50 mm (20mil)
	Sizes / Dimensions	7.25" x 48"
	Packaging / Emballage : Pieces Box / Boite	12
	Coverage / Surface : Sq.ft. Box / Pi.ca. Boite	29
	Weight / Poids : Kg Box / Boite	21.85







CONSTRUCTION

	Standard / Norme	ASTM F1700 : Class III, Type B, 5.5.1 Commercial Applications
	Installation	Glue Down / Collée
	Graphic Designs / Conception graphique	Hi-Definition Hardwood Design / Design bois haute définition
	Bevel Edge Profile / Profilé en biseau	Four Sides / Quatre côtés
	Surface Finish / Protection	PUR / UV PurKleen™ Ceramic Bead Protection : No Wax, No Spray Buff, for the life of the product Protection PUR / UV PurKleen™ particules de céramique : Pas de cirage, pas de vaporisation, pour la vie du produit

PERFORMANCE

	Chemical and Stain Resistance / Résistance chimique et aux taches	ASTM F925	Compliant / Conforme
	Abrasion Resistance / Résistance à l'abrasion	ASTM F510 / Group T 	Compliant / Conforme
	Slip Resistance / Résistance au glissement	ASTM D2047 / R9	Compliant / Conforme
	Static Load Resistance / Résistance à la charge statique	ASTM F970	Compliant / Conforme
	Residual Indentation / Indentation résiduelle	ASTM F1914	Compliant / Conforme
	Wheel Castor Resistance / Résistance chaise à roulettes	EN 425	Compliant / Conforme
	Dimensional Stability / Stabilité dimensionnelle	ASTM F2199	Compliant / Conforme
	In-floor Heating / Planchers chauffants	Suitable for hydronic heated floor systems, maximum ambient room temperature 25°C (77°F) Convient aux planchers chauffants hydroniques, température ambiante maximale 25°C (77°F)	
	Impact Insulation Class / Bruit de choc	ASTM E989	73 IIC
	Delta Rating / Valeur Delta	ASTM E2179	Δ24
	Flame Spread and Smoke Development / Propagation des flammes et Dégagement de fumée	CAN/ULC-S102.2 / ASTM E648 Class I / ASTM E662	Compliant / Conforme

ENVIRONMENTAL / ENVIRONNEMENT

	Phthalate Free / Sans Phthalate	EN 14372	Compliant / Conforme
	Indoor Air Quality, VOC Emission / Qualité air intérieur, émissions VOC	FloorScore® Certified / Certifié FloorScore®	
	Recycling / Recyclage	100% Recyclable	
	Plant Certifications / Certificats usines	ISO 9002, ISO14001, OHSAS 18001	
	Health and Safety / Hygiène et sécurité	Complies with REACH regulations / Conforme au règlement REACH	
	Limited Warranty / Garantie Limitée	Residential : Lifetime / Résidentiel : Pour la vie Commercial : 15 Years / Ans	