


GLAZED PORCELAIN WALL TILE

SABIL


Sabil brings the quiet beauty of nature into ceramic—where organic variation and rich texture create surfaces with depth and authenticity.




Floun




Vanilla




Cloud



Viridian



Ultra Marine





Jungle

STOCKED SIZES	\$ /SF	\$ /PC
1 x 6" FIT	\$23.97	\$1.07
2 x 6"	\$22.75	\$1.75



ecotile

Fit Flour 1 x 6" SBFL16			Fit Jungle 1 x 6" SBJG16		
Flour 2 x 6" SBFL26			Jungle 2 x 6" SBJG26		
Fit Vanilla 1 x 6" SBVN16		Note: Due to the nature of the material, there may be dimensional variations between pieces. For optimal results, please use 1.5mm (0.06") spacers. Grouting: The choice of using a quality grout is crucial. We recommend Custom Building Products Prism SCG. Maintenance & Cleaning: As a general guideline, powder detergents should not be used, nor wire wool or abrasive materials. Generally, a sponge will be sufficient with warm water and liquid neutral soap. Then rinse. Caution: Dark grout on light coloured tiles can scratch or stain the surface, please test a separate area before grouting your space. All sizes are approximate and items are sold by piece.			
Vanilla 2 x 6" SBVN26					
Fit Cloud 1 x 6" SBCL16					
Cloud 2 x 6" SBCL26					
Fit Viridian 1 x 6" SBVR16					
Viridian 2 x 6" SBVR26					
Fit Ultra Marine 1 x 6" SBUM16					
Ultra Marine 2 x 6" SBUM26					

	1 x 6" FIT	2 x 6"
\$ / SF	\$23.97	\$22.75
\$ / EA	\$1.07	\$1.75
Flour	SBFL16	SBFL26
Vanilla	SBVN16	SBVN26
Cloud	SBCL16	SBCL26
Viridian	SBVR16	SBVR26
Ultra Marine	SBUM16	SBUM26
Jungle	SBJG16	SBJG26

RECOMMENDED APPLICATIONS



Recommended applications do not include consideration of any technical installation requirements or safety standards for slopes and pool decks.
All tile products and setting materials should be selected and installed in compliance with manufacturers specifications and applicable use standards.
W – Wall. F – Floor. F¹ – **Flour coloured tiles only.**

TECHNICAL SPECIFICATIONS

V Rating (Variation)	Breaking Strength (ISO 10545-4)	Resistance to Deep Abrasion (ISO 10545-6)	Slip Resistance	Frost Resistance (ISO 10545-12)	Country of Origin	Ecotile
V3: Vanilla, Cloud & Viridian V4: Flour V5: Jungle, Ultra Marine	≥ 35 N/ mm ² ≥ 1300 N		DCOF < 0.42	Yes	Spain	Yes
Number of Faces	Thickness	Resistance to Surface Abrasion (ISO 10545-7)	Moisture Rating (MR)	Chemical Resistance	PEI (Wear Resistance)	Recycled Content
40	8.5 mm		MR 1	Minimum Class B	2: Jungle, Ultra & Marine 3: Vanilla, Viridian & Cloud 4: Flour	Flour: 56% Everything Else: 24%

Product specifications are supplied by the manufacturer and are subject to change without notice. AMES makes no representations or warranties as to the specifications of any product. Prices are subject to change without notice; please contact your AMES Sales Consultant for current prices.